

U29-400

Nexus Series S - Flexible Polyurethane Specialty Foam Grade

PRODUCT SPECIFICATIONS

- + Colour: Charcoal
- + Density: 29 kg/m³ nominal
- + Tensile Strength: 85 kPa min
- + Elongation: 100% min
- + Tear Resistance: 250 N/m min
- + Indentation Force on Deflection:
 - (i) 40% 400 ± 50 N
 - (ii) Indentation Factor 1.85 min
- + Compression Set:
 - (i) 90% 10% max
- + Resilience: 20 % min
- + Test Method: - refer AS2282



PREMIUM RANGE

- + Foam Grade U29-400 is a flexible polyether polyurethane foam.
- + U29-400 is designed specifically for use as a carpet underlay.
- + It is also suitable for high load bearing upholstery and packaging applications.

PREMIUM SERVICE

- + Personal, prompt service from experienced Kiwis, backed by new state of the art factory and facilities.
- + We do not make or sell furniture or bedding therefore we do not compete with you, we are here to help you grow your business – in confidence.
- + We are a 100% New Zealand company dedicated to helping New Zealand manufacturers compete in their markets.
- + We have a complete selection of foams designed for New Zealand conditions. Tested, durable, and warranted to you for up to 15 years.
- + Ask about our design service.